HIGH-EFFICIENCY COMMERCIAL STACK WASHER/DRYER



Featuring Microprocessor Controls



CET8000XQ 27" Electric Stack Washer/Dryer with Metercase CGT8000XQ 27" Gas Stack Washer/Dryer with Metercase

Machine Accepts the Following Compatible Payment Systems:

- —Coin-Drop
- —Card Reader
- –Non-Coin PaymentConfigurations
- Single Payment System
- 3.2 Cu. Ft. Capacity—Washer/ 6.7 Cu. Ft. Capacity Dryer
- Push-Button Controls
- Combination of 9 Cycle Wash Options
- Optional Pre-Wash/Extra Rinse

- Stainless Steel Wash Basket
- Automatic Load Balancing
- Built-In Over-Sudsing Protection
- Maximum Spin Speed Extracts
 More Water
- Reversible Door, Dryer Only
- Front Control Panel 20° Angle
- Front Serviceable
- Washer is ADA Compliant
- 3-Year Limited Parts Only Warranty*

SAVE SPACE AND CUT UTILITY COSTS

- Get a Full-Size High-Efficiency Washer and Super-Capacity Dryer in the Space of a Washer Alone
- Save Energy and Water with High Speed Spin Extraction

MICROPROCESSOR CONTROLS

- Easy To Program
- Simple One-Touch Cycle Selection
- Panel Displays Operating Instructions and Countdown of Remaining Cycle Time
- Front Control Panel 20° Angle

METERCASE

- Metercase Integrated Into Console
- Accepts Coin-Drop, Card Reader and Non-Coin Payment Configurations
- Single Payment System

STYLISH DESIGN

- Large Concave Windows
- Porcelain Finish

AUTOMATIC DETERGENT, SOFTENER AND BLEACH DISPENSER

HIGH-EFFICIENCY DESIGN OFFERS SIGNIFICANT UTILITY SAVINGS

- Save up to 60% Every Year** on Energy,
 Water and Sewer Costs
- ENERGY STAR®-Oualified
- CEE Tier II
- Modified Energy Factor: 2.26
 Water Factor: 4.4

^{**}Based on AHAM load sizes. Individual savings may vary.

HIGH-EFFICIENCY COMMERCIAL STACK WASHER/DRYER



Featuring Microprocessor Controls

Whirlpool® High-Efficiency Commercial Stack Washer/Dryer **Microprocessor Controls**


STACKED UNIT SPECIFICATIONS		
MODELS	CET8000XQ CGT8000XQ	
WASHER SPECIFICATIONS		
MOTOR		
120V, 60Hz, variable-speed, high-efficiency, switched reluctance	Yes	
Wash — HP (kWh)	.09 (.07)	
Extract — HP (kWh)	.54 (.40)	
Average kilowatt hour per cycle	0.07	
CAPACITY		
Volume — (liters)	3.2 (91)	
Diameter — in. (mm)	21.6 (547)	
Depth — in. (mm)	13.4 (341)	
Drain hose length — ft. (m)	6 (1.83)	
DRYER SPECIFICATIONS		
MOTOR		
Single-phase, thermoprotected against overload, auto-reset	Yes	
HP (kw)	¹ / ₄ (.19)	
Capacity — cu. ft. (cu. m)	6.7 (.17)	
AIRFLOW		
Electric models — cfm (cmm)	220 (6.2)	
Gas models — cfm (cmm)	230 (6.5)	
Tumble speed — RPM	50± 1	
EXHAUST DUCT DIAMETER — IN. (mm)	4 (101.6)*	
ELECTRICAL REQUIREMENTS		
CET model — Voltage	240V/60Hz	
CGT model — Voltage	120V/60Hz	
BREAKER/FUSE REQUIREMENTS		
CET model — Amps	30	
CGT model — Amps	15	
HEATING ELEMENT RATING		
CET model — Electric heating element – watts	5,600	
CGT model — BTU/hr. (kcal/hr.)	24,000 (6,048)	
ADJUSTABLE LEVELING LEGS	Yes	
COLOR		
White	Yes	
APPROXIMATE WEIGHT		
Crated — lbs. (kg)	383 (173)	
Uncrated — lbs. (kg)	372 (169)	
DIMENSIONS		
Width — in. (mm)	27 (686)	
Depth — in. (mm)	29.5 (749)	
Height — in. (mm)	74 (1880)	

^{*}Use a 4" (101.6mm) diameter rigid aluminum or galvanized steel duct. Never use plastic, nonmetal or combustible duct. Because of continuous product improvement, Whirlpool reserves the right to change specifications without notice.



3-YEAR LIMITED PARTS **ONLY WARRANTY**

For a period from the date of original purchase through the time listed above, the designated parts that fail in normal commercial use will be repaired or replaced free of charge for the part itself, with the owner paying all other costs, including labor, transportation and customs duty. Chemical damage is excluded from all warranty coverage. See complete warranty for details.



MAXIMUM EXHAUST DUCT LENGTH PER NUMBER OF TURNS

Number Of 90° Turns







Angled Hood

62 ft. (18.9 m) 57 ft. (17.4 m) 53 ft. (16.2 m)

51 ft. (15.6 m)

49 ft. (14.9 m)

Style

Rigid Metal Vent			
	Box Hood and	Angled Hood	
	Louvered Style	Style	
0	135 ft. (41.2 m)	129 ft. (39.3 m)	
1	125 ft. (38.1 m)	119 ft. (36.3 m)	
2	115 ft. (35.1 m)	109 ft. (33.2 m)	
3	106 ft. (32.3 m)	100 ft. (30.5 m)	
4	98 ft. (29.9 m)	92 ft. (28.0 m)	

Flexible Metal Vent Box Hood and

Louvered Style

76 ft. (23.2 m) 71 ft. (21.6 m) 67 ft. (20.4 m)

65 ft. (19.8 m)

63 ft. (19.2 m)











To Locate a Distributor Near You, Please Visit www.whirlpoolcommerciallaundry.com/distributor, or Call 1-800-NO-BELTS.